

CT-4591

self-adhesive paving strip membrane

Style 4591 is a self-adhesive paving strip membrane. We wish to advise that CT-4591 meets the following minimum average roll values (MARV) listed below:

Property	Test Method	Minimum Average Roll Value (English)	Minimum Average Roll Value (Metric)
Strip Tensile	ASTM-D-882 (modified)	50 lbs/in	8.76 kN/m
Puncture Resistance	ASTM-E-154	200 lbs	0.890 kN
Permeance - Perms	ASTM-E-96 method B	0.05 max	0.05 max
Pliability - 1/4" Mandrel 180° blend at -25°F	ASTM-D-146 (modified)	No cracks in fabric or rubberized asphalt	No cracks in fabric or rubberized asphalt

CT-4591 is manufactured in the USA. The values listed are a result of testing conducted in on-site laboratories in accordance with our quality control procedures (QEP). This information will be supplied to Civil-Tex Geosynthetics' original customer of record at the time of shipment

DATE ISSUED: 06/01/07

Exclusion of Liability

This publication should not be construed as engineering advice. While information contained in this publication is accurate to the best of our knowledge, Civil-Tex Geosynthetics does not warrant its accuracy or completeness. The only warranty made by Civil-Tex Geosynthetics for its products is set forth in our Certificate of Compliance that accompanies our shipment of the product, or such other written warranty as may be agreed by Propex Fabrics and individual customers. Civil-Tex specifically disclaims all other warranties, express or implied, including without limitation, warranties of merchantability or fitness for a particular purpose, or arising from provision of samples, a course of dealing or usage of trade.